

ARCHITECTURAL TRADITIONS

Crafted doors, windows and hardware.

Sikkens Cetol 1® & Cetol® 23 Plus Premium Alkyd System—Translucent Satin Finish

Cetol 1

Cetol 1 is a premium, translucent, exterior wood basecoat to be used with Cetol 23 Plus. Its superior oil alkyd formulation offers excellent penetration and adhesion to a vertical wood surface.

Cetol 23 Plus

Cetol 23 Plus is a premium, translucent topcoat for Cetol 1. The advanced alkyd resin with UV absorbers offers excellent durability and protection for siding and other vertical surfaces.

Features	Benefits
Translucent Iron Oxides	Improved clarity and color retention protection from “graying”
UV Absorbers	Added UV protection leads to less frequent maintenance
Microporous	Minimizes the occurrence of peeling and blistering
Translucent Film Forming System	Durable, rich “look” with a satin sheen

Currently available on Mahogany in eight colors Pricing: use Premium Chart

Maintenance Procedures

Proper maintenance starts with visual inspection. A timeframe of two to three years on the south and west exposures and three to four years on north and east exposures can be used as a general guideline. However, as weathering and exposure can vary widely, maintenance may be needed sooner and should be performed when visually necessary regardless of timeframe.

1. Spray the surface with clean water, wetting the wood.
2. Clean the surface with a solution of two ounces of 100% powdered Tri-Sodium Phosphate (TSP) or phosphate-free substitute plus one quart of liquid bleach in three quarts of water. Apply this solution generously to the wood with a garden pump sprayer.
3. Let the solution sit on the wood for 15-20 minutes. During this period, scrub the surface with a hard bristle brush to help remove mill glaze and/or weathering. Do not let the solution dry on the wood. Keep it wet.
4. Power wash the cleaning solution from the wood with clean water. To prevent damaging the wood, do not exceed 500 psi. The nozzle must be a maximum of one foot from the surface for full effectiveness.
5. Let the surface dry for three days before application (i.e., the moisture content is below 18%).
6. Apply one coat of Cetol 23 Plus.

Cetol 1 with Cetol 23 Plus has been the industry standard for beauty and durability for siding, log homes, fences, trim, etc., for decades. This time-tested formulation provides premium results.